



RAVENOL Motobike 4-T Mineral SAE 15W-40



ART.-NR. 1173121

1 L | 1173121-001
4 L | 1173121-004
20 L | 1173121-020
20 L | 1173121-B20
1000 L | 1173121-700

VISCOSITY 15W-40

SPECIFICATIONS API SN

APPROVALS JASO MA2 T903:2016 (M049RAV169)

RECOMMENDATIONS YAMAHA | KAWASAKI | HONDA | APRILIA | BMW | SUZUKI | DUCATI | TRIUMPH | MOTO-GUZZI

RAVENOL Motobike 4-T Mineral SAE 15W-40 is an engine oil on mineral oil base with excellent additives which was especially produced for 4 stroke motorbikes. With **RAVENOL Motobike 4-T Mineral SAE 15W-40** a solid and high loadable engine oil was developed for superior engines of motorbikes with wet couplings and oil lubricated couplings.

RAVENOL Motobike 4-T Mineral SAE 15W-40 has an excellent lubricating film adhesive capacity and a very good shear stability as well as an excellent cleaning power and a high aging resistance.

Application Notes

RAVENOL Motobike 4-T Mineral SAE 15W-40 is suitable as an engine oil for all motorbikes in case the specification SAE 15W-40 is requested.

Characteristics

RAVENOL Motobike 4-T Mineral SAE 15W-40 offers:

- a very good shear stability
- very good cold start characteristics
- a high oxidation stability
- prevention of black sludge accumulation
- an excellent viscosity temperature behaviour
- suitable for catalysts
- convincing detergent and dispersant characteristics
- high safety reserves even under boundary lubrication conditions

Property	Unit	Data	Audit
Density at 20°C	kg/m ³	863,6	EN ISO 12185
Colour		gelbbraun	visual



Property	Unit	Data	Audit
Viscosity at 40°C	mm²/s	107,8	DIN 51 562
Viscosity index VI		135	DIN ISO 2909
CCS Viscosity at -20°C		6124	ASTM D5293
Pourpoint	°C	-30	DIN ISO 3016
Flash point	°C	256	DIN ISO 2592
TBN	mg KOH/g	8,0	ASTM D2896
Sulphated ash	%wt.	1,06	DIN 51 575

All information correspond to the best of our knowledge to the actual situation of the cognitions and our development. Subject to alterations. All references made to DIN-norms are only for the description of the goods. There is no guarantee. In case there will be any problems please contact the technical service.

Release: : 10. December 2020