

MOL Engine Flushing Oil

flushing oil



MOL Engine Flushing Oil is a low viscosity refined lubricating oil containing no additives, which can be used for flushing internal combustion engines.

Application



Cleansing internal combustion engines and other oil spaces

Sliding and rolling bearings of low-duty machine elements

Features and benefits

Good detergent-dispersant properties

Prevents formation of lacquer and sludge type deposits

Specifications and approvals

Viscosity grade: ISO VG 15

Properties

Properties	Typical values
Density at 15°C [g/cm ³]	0,855
Kinematic viscosity at 40°C [mm ² /s]	15,1
Pour point [°C]	-12
Flash point (Cleveland) [°C]	190

The characteristics in table are typical values of the product and do not constitute a specification.

Storage and handling instructions

Store in the original container in dry, properly ventilated area. Keep away from direct flame and other sources of ignition. Protect from direct sunlight.

During transport, storage and use of the product follow the work safety instructions and environmental regulations relating to mineral oil products.

For further details please read the Material Safety Data Sheet of the product.

In the original container under the recommended storage conditions: 60 months

Recommended storage temperature: max. 40°C

Ordering information

Custom Tariff Number 27101999

SAP code and packaging:

13011209 MOL Engine Flushing Oil 1L

1 l plastic bottle (for order only)

Order booking:

Please contact your local distributor or sales partner for ordering details.