



RAVENOL Diesel Performance Optimizer Premium



ART.-NR. 1390241

300 ml | 1390241-300

RECOMMENDATIONS LEICHT MISCHBARES DIESEL-ADDITIV

RAVENOL Diesel Performance Optimizer Premium is a premium fuel additive for all diesel engines for cleaning the diesel system, increasing operational safety and for the economic feasibility of diesel engines.

RAVENOL Diesel Performance Optimizer Premium reduces CO₂ and HC emissions, which is tested and certified by the TÜV (Technical Inspection Agency) Nord.

RAVENOL Diesel Performance Optimizer Premium cleans the diesel system and the combustion chamber; this leads to a clean fuel injection system.

RAVENOL Diesel Performance Optimizer Premium enables saving fuel. The formation of "acidic" water is prevented and therefore, there is a higher level of protection against corrosion.

RAVENOL Diesel Performance Optimizer Premium increases the lubrication effect for low sulphur fuel.

RAVENOL Diesel Performance Optimizer Premium prolongs the service life of catalytic converters and lambda probes by means of optimum combustion.

Application Notes

RAVENOL Diesel Performance Optimizer Premium is added to the diesel fuel.

Area of application:

- Diesel engines in passenger cars and lorries
- Can be used preventively at every service
- For all diesel fuels, summer and winter diesel
- Suitable for modern common rail and pump nozzle systems
- Can also be used in bio-diesel or mixtures of diesel fuel with bio-diesel

Application: Pour the contents of the container into the tank. Fuel volume up to 50 litres of diesel. Minimum fuel capacity according to volume of fuel reserve.



Characteristics

RAVENOL Diesel Performance Optimizer Premium offers:

- Certified efficacy by the TÜV (Technical Inspection Agency) Thuringia for the reduction of CO₂ and HC emissions.
- Cleans diesel system and combustion chamber
- Saves fuel
- No "acidic" water, corrosion protection
- Increases the lubrication effect for low sulphur fuel
- Improves the ignitability and reduces "rattling sounds" caused by fuel

Property	Unit	Data	Audit
Density at 20°C	kg/m ³	842,0	EN ISO 12185
Colour		braun	visual
Flash Point PM	°C	45	DIN ISO 3679

All information correspond to the best of our knowledge to the actual situation of the cognitions and our development. Subject to alterations. All references made to DIN-norms are only for the description of the goods. There is no guarantee. In case there will be any problems please contact the technical service.

Release: : 10. December 2020