

Fully Synthetic



Kixx ATF Multi

Top Performance Multi-vehicle Automatic Transmission Fluid

JASO 1A, GM DEXRON®-III, TOYOTA T-IV, HYUNDAI SP-III/SP-IV

DESCRIPTION

Kixx ATF Multi is a high-performance, high-quality multi-vehicle fluid for automatic transmissions. (Applicable for Slip controlled lock-up clutch) It is a specially formulated fluid designed to meet the requirements of a wide range of Automatic Transmission Specifications requiring Hyundai SP-III, SP-IV, GM DEXRON® III, Ford MERCON®, Toyota T-IV and WS. In addition, it meets the requirements of European OEM's like Volvo CE 97340 and MB, BMW, VW, ZF 4, 5, 6 and 8-speed automatic transmission specifications. Kixx ATF Multi is a special blend of high quality base stocks with an advanced additives system for use as a Service-Fill.

PERFORMANCE STANDARDS

Auto Maker	Specification	Auto Maker	Specification
VW / Audi	G 052 162 (ZF Lifeguard 5)	Hyundai / Kia	Dex-II, SP-II
	G 055 162-A2, A6 (ZF Lifeguard 6 Plus)		JWS 3314, NWS 9838
Mercedes Benz	G 060 162 (ZF Lifeguard 8)	Jaguar	SP-III, SP-IV, SP-IV M, SP-IV RR
	G 052 990		ATF RED 1, RED 1K
BMW	G 055 025-A2 (JWS 3309)	JASO	ATF 3403 JLM20238
	MB 236.1, 236.2, 236.3		ATF 3403-M115
Ford	MB 236.5, 236.6, 236.7	Mazda	ATF LT71141, ZF 5HP 24
	MB 236.8, 236.9		M315-2013 1A
Fuso	7045E, ETL-8072B	Mitsubishi	M315-2013 2A
	JWS 3309 (T-IV)		ATF 3317
GM	LT71141(ZF 5 HP 18FL/19FL/24A/30)	Nissan	ATF D-II, F-1, FZ
	MERCON®, FNR5		ATF M-III, M-V, N-1, S-1
Honda	WSS M2C138CJ, M2C166H	Porsche	Diageen ATF PA
	WSS M2C 922A1, 924A		Diageen AW
Chrysler / Dodge	WSS M2C 938A	Subaru	Diageen J2, J3, SK
	ATF-A4		Diageen SP-II, SP-III, SP-IV
Isuzu	ATF-II	Toyota	Matic Fluid C, D, J
	ATF-SP III		Matic Fluid K, S
JEEP	DEXRON®-II, IID, IIE	ZF	ATF 3403-M115
	DEXRON®-III, IIIG, IIIG		T-IV (JWS 3309)
	GM/GMC/Opel/Saturn V6, AW1	Shell	ZF 5HP 19FL, 5HP 20, LT71141
	GM9986195(Aisin AW, JWS 3309)		ATF, ATF 5AT, ATF HP
	ATF Ultra II, DW-1	Texaco	ATF 2326, ATF 2384K
	ATF-Z1(except in CVTs)		ATF 3314, ATF 3317
	Type 3.0, Type 3.1		JWS 3309
	ATF+, +2		ATF D-II, D-III, T-III, T-IV(JWS 3309)
	ATF +3(MS 7176E), +4(MS 9602)		ATF WS(JWS 3324)
	JWS 3309 (T-IV)		4~9 speed transmission
	Besco ATF-II		TE-ML 05L, 09, 11A, 11B, 21L
	Besco ATF-III		3403, M115, LA 2634
	ATF+3, +4		7045-E, 8072B, N402

CUSTOMER BENEFITS


- Excellent anti shudder protection.
- Oxidation and thermal stability
- Provides high foam stability.
- Provides good start operation in cold climates thanks to its excellent low-temperature fluidity.
- Provides more stable friction property.
- Use for most 4~8 speed vehicles.

KEY PROPERTIES

Density, kg/L @15°C	0.845
Kinematic Viscosity, mm ² /s @ 40°C	35.6
Kinematic Viscosity, mm ² /s @ 100°C	7.0
Pour Point °C	-49
Flash Point °C	220
Brookfield Viscosity, cP @-20°C	875
Brookfield Viscosity, cP @-40°C	14,960
Package (Liters)	1, 4, 4T, 20, 200

UNIQUE FEATURES

Kixx ATF Multi has demonstrated superior oxidation stability performance in various industrial requirements.



Kixx ATF Multi provides Excellent Shear Stability performance exceeds the requirements of European OEMs.

