



RAVENOL Standard Truck SAE 10W



ART.-NR. 1123610

20 L | 1123610-020
20 L | 1123610-B20
1000 L | 1123610-700

SPECIFICATIONS API CF | API SF

FABRICATION MINERAL

RECOMMENDATIONS MB 227.0 | CATERPILLAR TO-2 | ALLISON C4 | MIL-L-2104 E | MAN 270 | MTU TYPE 1 | VOITH RETARDER A | VOITH DIWA | ZF TE-ML 02C, 03B, 04B, 06A, 07D

RAVENOL Standard Truck SAE 10W is mineral mono grade motor oil for trucks. All-season oil for all truck diesel engine types. High protection against friction and abrasion, excellent cold start characteristics. Extended oil change intervals according to manufacturer's recommendations.

Application Notes

RAVENOL Standard Truck SAE 10W is mono grade motor oil for use in truck diesel engines. Also suitable for stationary plants.

Characteristics

RAVENOL Standard Truck SAE 10W offers:

- Good shear stability
- High oxidation stability
- Excellent viscosity temperature behaviour
- Convincing detergent and dispersant characteristics
- High safety reserves
- Good cold start characteristics
- Best corrosion protection
- Suitable for catalysis

Property	Unit	Data	Audit
Colour		gelbbraun	visual
Density at 20°C	kg/m ³	862	EN ISO 12185
Viscosity at 40°C	mm ² /s	36,9	DIN 51 562



Property	Unit	Data	Audit
Viscosity at 100°C	mm ² /s	62,3	DIN ISO 2952
Pourpoint	°C	-36	DIN ISO 3016
Flash point (COC)	°C	232	DIN ISO 2592
TBN	mg KOH/g	12,0	ASTM D2896

All information correspond to the best of our knowledge to the actual situation of the cognitions and our development. Subject to alterations. All references made to DIN-norms are only for the description of the goods. There is no guarantee. In case there will be any problems please contact the technical service.

Release: : 16. October 2019