



RAVENOL SNOWMOBILES Teilsynth. 2-Takt



ART.-NR. 1152310

1 L | 1152310-001
4 L | 1152310-004
10 L | 1152310-010
20 L | 1152310-020
20 L | 1152310-B20
1000 L | 1152310-700

SPECIFICATIONS API TC | ISO-L-EGC

FABRICATION SEMI-SYNTHETIC

APPROVALS JASO FC (049RAV152)

RECOMMENDATIONS SUZUKI | YAMAHA | KAWASAKI | ARCTIC CAT |
BOMBARDIER | SKI-DOO | POLARIS

RAVENOL SNOWMOBILES Teilsynth. 2-Takt is high quality 2-stroke engine oil with special esters and Polyisobutylene (PIB) based on high quality base oils with an ash less additive package for optimum lubricity and excellent corrosion protection.

Application Notes

RAVENOL SNOWMOBILES Teilsynth. 2-Takt is recommended for typical mixing ratio: 1: 75

RAVENOL SNOWMOBILES Teilsynth. 2-Takt is particularly suitable for the lubrication of air-cooled two-stroke gasoline engines with high speed and heavy load.

RAVENOL SNOWMOBILES Teilsynth. 2-Takt is ideal for lubricating two-stroke snowmobiles with suitable water cooling.

Characteristics

RAVENOL SNOWMOBILES Teilsynth. 2-Takt offers:

- proper lubrication of all engine parts
- a strong cleaning effect, the combustion chambers and inlet and outlet ports freeing up largely of combustion residues and deposits
- contains additives, designed on clean spark plugs ensure optimal performance of the engines
- an excellent corrosion
- a very high wear and corrosion protection
- low exhaust emissions through good combustion

- Immediate, homogeneous mixture with the used fuel (including lead-free)



Property	Unit	Data	Audit
Density at 20°C	kg/m ³	863,0	EN ISO 12185
Colour		blau	visual
Viscosity at 100°C	mm ² /s	9,6	DIN 51 562
Viscosity at 40°C	mm ² /s	70,1	DIN 51 562
Viscosity index VI		117	DIN ISO 2909
Pourpoint	°C	-36	DIN ISO 3016
Flash point (COC)	°C	180	DIN ISO 2592

All information correspond to the best of our knowledge to the actual situation of the cognitions and our development. Subject to alterations. All references made to DIN-norms are only for the description of the goods. There is no guarantee. In case there will be any problems please contact the technical service.

Release: : 16. March 2021