# **MOL Hidrofluid B** automatic transmission fluid



MOL Hidrofluid B is an automatic transmission fluid produced from highly refined base oils, containing additives corresponding to the load.

Hydrodynamic clutches

Hydraulic servo equipment

Gear drives, torque converters and hydraulic systems

Railway gear drives

#### **Application**



## atures and benefits

Features and benefits	
Good wear protection	Reliable equipment protection and long machine lifetime
Good thermal and oxidation stability	No harmful deposits are formed even at high temperatures
Excellent corrosion protection	Extreme long term protection of steel and non-ferrous metal parts
Low foaming tendency	Stable, continuous lubricating film, giving reduced wear

#### **Properties**

Properties	Typical values
Density at 15°C [g/cm3]	0,871
Kinematic viscosity at 40°C [mm2/s]	30,0
Kinematic viscosity at 100 °C [mm2/s]	5,4
Viscosity index	115
Pour point [°C]	-39
Flash point (Cleveland) [°C]	200

The characteristics in table are typical values of the product and do not constitute a specification.

## Storage and handling instructions

Store in the original container in dry, properly ventilated area. Keep away from direct flame and other sources of ignition. Protect from direct sunlight.

During transport, storage and use of the product follow the work safety instructions and environmental regulations relating to mineral oil products.

For further details please read the Material Safety Data Sheet of the product.

Gear oils are finished lubricant formulations where additional additives are unnecessary and may result in unforeseeable adverse effects. The manufacturer and distributor shall not be held liable for such possible damages. In the original container under the recommended storage conditions: 60 months Recommended storage temperature: max. 40°C

## **MOL Hidrofluid B** automatic transmission fluid



60 I steel drum

216.5 | steel drum

IBC (for order only)

#### **Ordering information**

Custom Tariff Number 27101987

#### SAP code and packaging:

 13100168
 MOL Hidrofluid B 50KG

 13100169
 MOL Hidrofluid B 180KG

 13301268
 MOL Hidrofluid B 860KG

#### Order booking:

Please contact your local distributor or sales partner for ordering details.

Manufactured and distributed by MOL-LUB Ltd. E-mail: lubricants@mol.hu Web: www.mol.hu/en Technical service: H-1117 Budapest, Neumann János u. 1/E. Tel: + 36 (1) 464-02-36 E-mail: lubtechdesk@mol.hu Latest revision: 2018.10.25 13:35