

# MOL Standard Diesel 20W-40

## multigrade diesel motor oil



MOL Standard Diesel 20W-40 is a multigrade diesel engine oil, produced from mineral base oils, containing additives that modify the flow characteristics and ensuring appropriate performance levels, for use in older naturally aspirated diesel engines.

### Application



Low- and medium-duty trucks, buses, agricultural and road construction machines, which do not have a turbocharger

Naturally aspirated diesel engines of older construction

### Features and benefits

Multigrade engine oil

All-season application; improved cold start compared to monograde engine oils

High operational viscosity

Reduces oil consumption and improves internal sealing of the engine

Good lubricating film strength

Stable load-carrying lubricating film even in heavily worn, older engines

### Specifications and approvals

Viscosity grade: SAE 20W-40  
API CC  
MIL-L-2104B

### Properties

Properties	Typical values
Density at 15°C [g/cm <sup>3</sup> ]	0,889
Kinematic viscosity at 40°C [mm <sup>2</sup> /s]	135,6
Kinematic viscosity at 100 °C [mm <sup>2</sup> /s]	14,8
Viscosity index	110
Pour point [°C]	-27
Flash point (Cleveland) [°C]	220
Base number (BN) [mg KOH/g]	6,6

The characteristics in table are typical values of the product and do not constitute a specification.

# MOL Standard Diesel 20W-40

## multigrade diesel motor oil



### Storage and handling instructions

Store in the original container in dry, properly ventilated area. Keep away from direct flame and other sources of ignition. Protect from direct sunlight.

During transport, storage and use of the product follow the work safety instructions and environmental regulations relating to mineral oil products.

For further details please read the Material Safety Data Sheet of the product.

Engine oils are finished lubricant formulations where additional additives are unnecessary and may result in unforeseeable adverse effects. The manufacturer and distributor shall not be held liable for such possible damages.

In the original container under the recommended storage conditions: 60 months

Recommended storage temperature: max. 40°C

### Ordering information

Custom Tariff Number 27101981

#### SAP code and packaging:

13011137	MOL Standard Diesel 20W-40 1L	1 l plastic bottle
13006526	MOL Standard Diesel 20W-40 X4L	4 l plastic can
13007238	MOL Standard Diesel 20W-40 10LA	10 l plastic can
13006527	MOL Standard Diesel 20W-40 50KG	60 l steel drum
13006523	MOL Standard Diesel 20W-40 180KG	216.5 l steel drum
13007064	MOL Standard Diesel 20W-40	Road tank car (for order only)

#### Order booking:

Please contact your local distributor or sales partner for ordering details.