

MOL Essence 15W-40

multigrade motor oil



MOL Essence 15W-40 is a state-of-art product made from high performance refined mineral base oils that provide triple antioxidant protection, using a complex additive system, developed for passenger cars and commercial vehicles.

Application



Naturally aspirated or turbocharged, gasoline, diesel and gas engines in passenger cars and light commercial vehicles (<3.5 t weight)

Features and benefits

Triple antioxidant protection

Prevents presence of free radicals responsible for oil ageing, through triple anti-oxidant action, increasing the service life of the motor oil and the engine

Excellent shear stability

Preserves viscosity properties during the entire oil change period

Specifications and approvals

Viscosity grade: SAE 15W-40
API SJ/CF

Properties

Properties	Typical values
Density at 15°C [g/cm ³]	0,879
Kinematic viscosity at 40°C [mm ² /s]	109,6
Kinematic viscosity at 100 °C [mm ² /s]	14,4
Pour point [°C]	-27
Flash point (Cleveland) [°C]	230

The characteristics in table are typical values of the product and do not constitute a specification.

Storage and handling instructions

Store in the original container in dry, properly ventilated area. Keep away from direct flame and other sources of ignition. Protect from direct sunlight.

During transport, storage and use of the product follow the work safety instructions and environmental regulations relating to mineral oil products.

For further details please read the Material Safety Data Sheet of the product.

Engine oils are finished lubricant formulations where additional additives are unnecessary and may result in unforeseeable adverse effects. The manufacturer and distributor shall not be held liable for such possible damages.

In the original container under the recommended storage conditions: 60 months

Recommended storage temperature: max. 40°C

MOL Essence 15W-40

multigrade motor oil



Ordering information

Custom Tariff Number 27101981

SAP code and packaging:

13011122	MOL Essence 15W-40 1L	1 l plastic bottle
13008770	MOL Essence 15W-40 X4L	4 l plastic can
13008408	MOL Essence 15W-40 180KG	216.5 l steel drum

Order booking:

Please contact your local distributor or sales partner for ordering details.