

# MOL Formoil FL H2

## mould release oil



MOL Formoil FL H2 is a formwork separating auxiliary material containing additives that prevent sticking and corrosion. It prevents sticking of concrete element to the template, thus making the removal and cleaning of the formwork easier. It provides temporary corrosion protection to steel templates between later applications. If the thickness of the lubricating layer applied to the template is greater than required, oily stains may occur on the concrete elements. The auxiliary material can be applied also on hot templates (80 - 90 °C).

### Application



Manufacturing of concrete products  
Manufacturing of rod-like products

### Features and benefits

Application specific composition	Prevents moulded material from getting stuck to the mould Quick and easy stripping without damaging edges and vertices
Easy to lay on surfaces	Application to the mould surface is possible by spraying, rolling or brushing
Good flow properties	Applicable both outdoors and indoors
Good corrosion protection	Prevents rusting of mould elements and increases their lifetime
Economical use	Specific lubricant demand: 50-80 m <sup>2</sup> /kg, depending on the lubrication technology and the mould material

### Specifications and approvals

ISO-L-B

### Properties

Properties	Typical values
Appearance	light yellow, clear
Density at 15°C [g/cm <sup>3</sup> ]	0,861
Kinematic viscosity at 40°C [mm <sup>2</sup> /s]	20,9
Pour point [°C]	-12
Flash point (Cleveland) [°C]	195

The characteristics in table are typical values of the product and do not constitute a specification.

### Storage and handling instructions

Store in the original container in dry, properly ventilated area. Keep away from direct flame and other sources of ignition. Protect from direct sunlight.

During transport, storage and use of the product follow the work safety instructions and environmental regulations relating to mineral oil products.

For further details please read the Material Safety Data Sheet of the product.

In the original container under the recommended storage conditions: 36 months

Recommended storage temperature: max. 40°C

# MOL Formoil FL H2

## mould release oil



### Ordering information

Custom Tariff Number 27101999

#### SAP code and packaging:

13009377 MOL Formoil FL H2 170KG

216.5 l steel drum

#### Order booking:

Please contact your local distributor or sales partner for ordering details.