



RAVENOL Automatik-Getriebeöl ATF Type J2/S Fluid



ART.-NR. 1211115

1 L | 1211115-001
4 L | 1211115-004
10 L | 1211115-010
20 L | 1211115-020
20 L | 1211115-B20
60 L | 1211115-060
60 L | 1211115-D60
208 L | 1211115-208
208 L | 1211115-D28
1000 L | 1211115-700

FABRICATION SYNTHETIC

RECOMMENDATIONS NISSAN KE908-99932 MATIC FLUID J | NISSAN KLE2300002 MATIC FLUID J | NISSAN 999MP-MTJ00P MATIC FLUID J | NISSAN 999MP-MTS00P MATIC FLUID S | NISSAN KLE24 00002 MATIC FLUID S | MITSUBISHI MZ 313771 ATF FLUID J2 | MITSUBISHI 4031610 ATF FLUID J3 | RENAULT MATIC J6

RAVENOL ATF J2/S Fluid is a synthetic ATF (Automatic Transmission Fluid), designed on the basis of high quality hydrocrack oils with a special additive and inhibition, which ensure a perfect function of the automatic Transmission.

RAVENOL ATF J2/S Fluid is specifically designed for all 5, 6 and 7-speed JATCO automatic transmissions.

RAVENOL ATF J2/S Fluid ensures maximum wear protection and smooth shifting in all conditions.

RAVENOL ATF J2/S Fluid is red colored.

Application Notes

RAVENOL ATF J2/S Fluid is designed specifically for use in JATCO automatic transmissions as follows;
JF613E - Renault gearbox AJ0 Laguna, Scenic, Espace, Latitude;
Nissan Qashqai transmission AJ0;
Mitsubishi Outlander Transmission F6AJA and W6AJA;
JR710E and JR711E - Infiniti FX50, EX37, NISSAN FAIR LADY Z, SKYLINE, FUGA.

Characteristics

RAVENOL ATF J2/S Fluid offers:

- Excellent lubricity even at low temperatures in winter
- High and stable viscosity index
- Very good oxidation stability
- Extensive protection against wear, corrosion and foaming
- High thermal and oxidative stability
- An excellent cooling capability.



Property	Unit	Data	Audit
Density at 20°C	kg/m ³	838,0	EN ISO 12185
Colour		rot	visual
Pourpoint	°C	-51	DIN ISO 3016

All information correspond to the best of our knowledge to the actual situation of the cognitions and our development. Subject to alterations. All references made to DIN-norms are only for the description of the goods. There is no guarantee. In case there will be any problems please contact the technical service.

Release: : 20. October 2020