



RAVENOL SCR 32 Screw Kompressorenöl



ART.-NR. 1330304

5 L | 1330304-005
20 L | 1330304-020

SPECIFICATIONS KENNZEICHNUNG NACH DIN 51 502: HLP DIN 51 524, TEIL 2 |FZG-TEST A 8,3/90: DIE 12. LASTSTUFE WIRD SICHER ERREICHT
FABRICATION MINERAL

RAVENOL SCR 32 Screw Kompressorenöl is optimal alloyed mineral screw compressor oil, with a high performance level and a wide application area of the whole industry. It is characterised by good viscosity temperature behaviour, a high aging resistant and a solid corrosion protection. Efficient additives offer an excellent corrosion protection even under extreme loads. The behaviour of sealing materials is neutral.

Application Notes

RAVENOL SCR 32 Screw Kompressorenöl is used in compressors.

Characteristics

RAVENOL SCR 32 Screw Kompressorenöl offers:

- a high performance level
- a very good viscosity temperature behaviour
- a high aging resistant
- an excellent corrosion protection
- a solid corrosion protection
- neutrality of sealing materials

Property	Unit	Data	Audit
Density at 20°C	kg/m ³	867,7	EN ISO 12185
Colour		hellgelb	visual
Viscosity at 100°C	mm ² /s	5,4	DIN 51562
Viscosity at 40°C	mm ² /s	32,1	DIN 51 562
Viscosity index VI		102	DIN ISO 2909



Property	Unit	Data	Audit
Pourpoint	°C	-30	DIN ISO 3016
Flash point (COC)	°C	224	DIN ISO 2592
FZG-Test A/8,3/90 damage loading step		12	DIN 51 354
Aging stability, TOST	st	2000	DIN 51 587

All information correspond to the best of our knowledge to the actual situation of the cognitions and our development. Subject to alterations. All references made to DIN-norms are only for the description of the goods. There is no guarantee. In case there will be any problems please contact the technical service.

Release: : 18. January 2021