

## PerFormance Proofer Oil

### Product Overview

**PerFormance Proofer Oil** is an NSF® H1 registered fully synthetic food grade oil specifically designed to provide extremely high performance in the lubrication of bakery continuous conveyerized Proofer chains and other food processing equipment in humid and wet environments.

**PerFormance Proofer Oil** contains unique additives to prevent acidic corrosion. The product has excellent water resistance and tackiness additives to ensure non drip performance during use.



### Features and Benefits

- Audit compliant - NSF® H1 Registered
- Unaffected by water
- Excellent Rust & corrosion protection
- Excellent EP & anti wear additives lower chain wear and extends chain life
- Excellent Adhesion – Non drip
- Temperature range -30 °C to 165 °C
- Halal Certified
- Kosher Certified

### Applications

**PerFormance Proofer Oil** is particularly suited for the lubrication of:

- Continuous Proofer Chains
- Drive chains
- Conveyor chains
- Operating in ambient to low temperature environments

### Available Pack Sizes

Pack Size	Product Code
20Ltr	FG40400
205Ltr	FG40468



Nonfood Compounds  
Program Listed H1  
NSF Registration No 161020

## Typical Properties

Appearance	Off White Tacky Oil
Base Oil	Fully Synthetic Food Grade Oil
ISO Grade	100
Kinematic Viscosity @ 40°C, cSt  (ASTM4451)	101
Anti Wear	FZG Load Stage 12
Temperature range	- 30°C to + 165°C
VI	138
Evaporation Loss (205°C 6.5 Hrs)	4%

## Health and Safety

To obtain Material Safety Data Sheet (MSDS), contact our technical team

This Information is given in good faith but without warranty as the use of the product is outside the control of Performance Fluids Ltd

Revision SB 210222

**Performance Fluids Ltd**

**T:** +44(0) 1282 878240

**E:** sales@performancefluids.co.uk

**W:** www.performancefluids.co.uk



Certificate Number: 4769-QMS-001  
ISO 9001:2015  
Certificate Number: 4769-EMS-001  
ISO 14001:2015  
Certificate Number: 4769-HSI-001  
ISO 45001:2018 SSIP



**Innovators in Lubrication Design**