





RAVENOL ATF M 9-FE Serie



ART.-NR. 1211127

4 L | 1211127-004 10 L | 1211127-010 20 L | 1211127-020 20 L | 1211127-B20 1000 L | 1211127-700 FABRICATION SYNTHETIC

APPROVALS MB-APPROVAL 236.15

RECOMMENDATIONS ATF 134 FE | ATF 7134 FE | MB A 001 989 77 03 |
MB A 001 989 78 03

RAVENOL ATF M 9-FE Serie is a synthetic ATF (Automatic Transmission Fluid), designed on the basis of high quality hydrocrack oils with a special additive and inhibition, which ensure a perfect function of the automatic transmission.

RAVENOL ATF M 9-FE Serie is special formulation of automatic transmission oil ATF for use in special Mercedes Automatic-Transmission 7G-TRONIC with ECO Stop-Start (NAG2FE+). It guarantees in any mode for maximum wear protection.

Application Notes

RAVENOL ATF M 9-FE is suitable for use in special automatic transmission of Mercedes Automatic-Transmission 7G-TRONIC with ECO Stop-Start (NAG2FE+).

Characteristics

RAVENOL ATF M 9-FE offers:

- Very good lubricating ability even at low temperatures in winter
- A high, stable viscosity index
- Very good oxidation stability
- Protection against corrosion and foam formation
- · Good balanced coefficient of friction
- A high thermal and oxidative stability
- An excellent cooling capacity.
- RAVENOL special transmission fluid is special development for special gear and cannot be selected on the basis of technical parameters (viscosity, etc.). Therefore the decision was made not to give technical data.
- <u>Please note:</u> RAVENOL special transmission fluid is exclusively to apply under the original number, as indicated in the product information. Not sure of the correct transmission fluid, you can ask your garage or the car dealer with respect to the original OEM gear type and number or consult our advisers. It must be specified the VIN code (Vehicle Identification Number) of your vehicle.

- Certificate / Product Information -







- · Misapplication of RAVENOL special transmission fluid can lead to malfunction of the transmission shifting problems, increased fuel consumption, unwanted slip behavior, etc. cause and cause the failure of the transmission.
- Ravensberger Schmierstoffvertrieb GmbH does not liable for transmission failures in case of wrong selection of RAVENOL special transmission fluid.

Property	Unit	Data	Audit
Density at 20°C	kg/m³	842,0	EN ISO 12185
Colour		blau-grün	visual
Pourpoint	°C	-42	DIN ISO 3016

All information correspond to the best of our knowledge to the actual situation of the cognitions and our development. Subject to alterations. All references made to DIN-norms are only for the description of the goods. There is no guarantee. In case there will be any problems please contact the technical service.

Release: : 15. December 2020