











TECHNICAL DATA SHEET

AIMOL X-Line

Full synthetic engine oil for gasoline engines of passenger cars

APPLICATION

AIMOL X-Line is a full synthetic long-life engine oil on mid-saps technology suitable for cars with catalytic converters, turbo compressed engines and direct injection systems. It provides high protection even during long drain intervals, also for turbocharged engines.

AIMOL X-Line is suitable for modern hybrid cars, for example Toyota, Honda and Lexus. For some severe applications, like stop-and-go or heavy loads, drain intervals should substantially be decreased. This is described in OEM's manuals. This oil is not suitable for diesel particulate filters.

AIMOL X-Line has the following attractive properties:

- Outstanding protection to wear;
- Suitable for long drain intervals (based O.E.M. prescription);
- Excellent protection against dirt, sludge and deposits;
- Good anti-rust and oxidation properties;
- Suitable for use with gasoline containing up to 85% ethanol;
- Fuel saving properties.

PERFORMANCE LEVELS

AIMOL X-Line meets or exceeds the following performance levels/specifications:

API-services SN; SN-RC **ILSAC** GF-5

For 5W-20 also:

GM Dexos 1

GM LL-A-025, GM 6094M, GM 4718M

AVAILABLE PACKS New drum 205 Litre

Can 20 Litre

Can 4 Litre (4 cans per carton) Can 1 Litre (12 cans per carton)

TYPICAL FIGURES

	0W-20	5W-20
Density at 20°C kg/m ³	0.844	0,847
Viscosity at 40°C in cSt	43.7	44.6
Viscosity at 100°C in cSt	8.5	8.5
Viscosity Index	175	170
Flashpoint COC °C	>200	>205
Pour point in °C	<-40	<-40
TBN mg KOH/g (ASTM D2896)	8.5	8.5

ANGLO INTERNATIONAL MINING B.V Haringvliet 543, 3011 ZP Rotterdam The Netherlands

Version 23/1/2015

T +31 (0)10 28 27 927 E-mail: info@aimol.nl

www.aimol.nl













TECHNICAL DATA SHEET

HEALTH AND SAFETY

AIMOL X-Line has no adverse health effects provided it is used as directed.

TECHNICAL DATA INFO LINE

Should you require additional information or advice on AIMOL products, please contact us as per the details below

DISCLAIMER

Typical figures as indicated may vary per production cycle and can change at manufacturers' option. Specifications, however, are guaranteed. Because of continuous product research and development, the information within this data sheet is subject to change without any notification. Although every effort is made to ensure accurate information, A.I.M. by accepts no liability for any loss or damage suffered caused by the incorrectness and/or incompleteness of this text, and as a result of using this product for any application other than explicitly stated in this data sheet.

T +31 (0)10 28 27 927 E-mail: info@aimol.nl

www.aimol.nl