



## RAVENOL Fließverbesserer



**RAVENOL Fließverbesserer** can be mixed and is compatible with all diesel fuels (except Biodiesel) as well as fuel oils EL. Higher dosings as recommended are harmless. Demixing won't occur.

Practical experiences show that under consideration of the different kind of diesel fuels and fuel oils EL offered on the market following cold properties are given.

ART.-NR. 1430220

1L | 1430220-001

5L | 1430220-005

250ml | 1430220-250

## Application Notes

	Addition: Liter Ravenol Fließverbesserer per to Liter	Operating temperature operatur
Summer- Diesel fuel as well as fuel oil EL	1 : 1000 *)	- 10°C
	2 : 1000	- 18°C
	3 : 1000	- 23°C
	4 : 1000	- 25°C
Winter-	1 : 1000	- 25°C



Diesel-fuel	2 : 1000	28°C
	3 : 1000	31°C

\*) The cold properties depend on the used DK respectively fuel oil EL. When admixing in a ratio of 1:1000 normally an improvement of the cold properties by 5 °C to 10 °C are possible.

## Characteristics

The basic advantages of **RAVENOL Fließverbesserer** are:

- complete restless burning
- no erosion of the flammability
- no change of the hazard category
- no reduction of the viscosity, no illegal wastage in the pump

Property	Unit	Data	Audit
----------	------	------	-------

All information correspond to the best of our knowledge to the actual situation of the cognitions and our development. Subject to alterations. All references made to DIN-norms are only for the description of the goods. There is no guarantee. In case there will be any problems please contact the technical service.

Release: : 13. November 2019