MOL Dynamic Garden 2T

two-stroke motor oil



MOL Dynamic Garden 2T is a synthetic pre-diluted two-stroke engine oil, produced from highly refined base oils and high performance additives, for use in small gardening machines. It meets and even outperforms the engine oil specifications issued by the leading manufacturers of small gardening machines, such as MTD, Briggs & Stratton, Honda, and Tecumseh. It provides appropriate lubrication in mixture operated systems when the mixing ratio specified by the manufacturer in the service instructions is used. The use of MOL Dynamic Garden 2T is not recommended in mixture lubricated two-stroke engines working with fuels containing bio-ethanol (E85).

Application



Two-stroke engines of small garden equipment (rotary hoes, lawn mowers, brushcutters, hand chainsaws, power generators etc.)

Features and benefits

Contains a self-mixing additive

Low ash content

Outstanding cleaning effect

Entirely miscible with fuel

Reduces emission of smoke and harmful gases from the engine

Constantly ensures piston and combustion chamber cleanliness and free movement of piston rings

Specifications and approvals

API TC+ JASO FD CEC TSC-3 ISO-L-EGD

Properties

Properties	Typical values
Density at 15°C [g/cm3]	0,868
Kinematic viscosity at 40°C [mm2/s]	60,0
Kinematic viscosity at 100 °C [mm2/s]	8,7
Pour point [°C]	-36
Flash point (Cleveland) [°C]	90
Sulphated ash [mass %]	0,05

The characteristics in table are typical values of the product and do not constitute a specification.

1 / 2 Page.

Version: 015.001.000

MOL Dynamic Garden 2T

two-stroke motor oil



Storage and handling instructions

Store in the original container in dry, properly ventilated area. Keep away from direct flame and other sources of ignition. Protect from direct sunlight.

During transport, storage and use of the product follow the work safety instructions and environmental regulations relating to mineral oil products.

For further details please read the Material Safety Data Sheet of the product.

Engine oils are finished lubricant formulations where additional additives are unnecessary and may result in unforeseeable adverse effects. The manufacturer and distributor shall not be held liable for such possible damages. In the original container under the recommended storage conditions: 60 months

Recommended storage temperature: max. 40°C

Ordering information

Custom Tariff Number 27101981

SAP code and packaging:

13006095 MOL Dynamic Garden 2T X0,6L 0,6 I plastic bottle 13006941 MOL Dynamic Garden 2T 0,1L

Order booking:

Please contact your local distributor or sales partner for ordering details.

2 / 2 Page.

Version: 015.001.000