

Kixx Grease Liplax

Automotive Wheel Bearing & Chassis Grease
NLGI 2, GC-LB



DESCRIPTION

Kixx Grease Liplax is a premium, multipurpose EP automotive wheel bearing and chassis grease containing a lithium complex thickener, EP additives, rust and oxidation inhibitors and tackiness additives. It is red in color.

APPLICATIONS

- Automotive wheel bearings
- Chassis lubrication
- Highway and off-highway applications
- Construction equipment
- Agricultural tractors
- Heavy-duty transport
- General industrial greasing

Usable temperature range in continuous service: -30 to 165°C
Maximum temperature for short term exposure is 220°C.

PERFORMANCE STANDARD

- NLGI Service Category GC-LB

CUSTOMER BENEFITS

Saves maintenance costs

Effective EP additive protects against bearing wear under severe conditions and shock loading. The effective rust and corrosion inhibitors protect metal surfaces, even in conditions of severe water exposure.

Minimizes downtime

High dropping point minimizes leakage from bearings at elevated temperatures and excellent oxidation resistance ensures long grease life. The natural water resistance of the lithium complex thickener, combined with the additional tackiness additive, prevents water washout.

Minimizes inventory costs

Multipurpose capability allows use in a wide range of automotive and industrial applications, reducing the number of different greases required and eliminating product misapplication.

KEY PROPERTIES

NLGI Grade	2
Dropping Point, °C	263
Oil Viscosity, mm ² /s @ 40°C	200
Penetration, Worked @ 25°C	280
Thickener Type	Lithium Complex
Thickener (Lithium Complex), m %	11
Water Washout @ 79°C, 1hr	0.65
4 ball EP, kgf	250
Package (kg)	15, 180