



Mobil 1 0W-20

Mobil Passenger Vehicle Lube , Russia

Advanced Full Synthetic Motor Oil

Product Description

Mobil 1™ 0W-20 is an advanced full synthetic engine oil designed to help deliver outstanding engine protection and enhanced fuel economy. Mobil 1 0W-20 meets or exceeds the requirements of various vehicle manufacturers and industry standards and outperforms conventional oils. Mobil 1 0W-20 is recommended for SAE 0W-20 and 5W-20 applications.

Features and Benefits

Mobil 1 0W-20 is engineered with a proprietary blend of high performance synthetic basestocks fortified with a precisely balanced component additive system. The low viscosity, advanced full synthetic formulation helps to increase engine efficiency and improve fuel economy. Mobil 1 0W-20 provides the high-temperature protection of higher viscosity oils while offering the best fuel economy in the Mobil 1 line. Key features and potential benefits include:

Features	Advantages and Potential Benefits
Low viscosity, advanced full synthetic formula	Helps improve fuel economy based on 0.2-2.3% potential fuel economy improvement obtained by switching from higher viscosity oils to a 0W-20 grade. Actual savings are dependent upon vehicle/engine type, outside temperature, driving conditions and your current engine oil viscosity
Outstanding thermal and oxidation stability	Helps to reduce oil aging resulting in long lasting protection
Outstanding low temperature capabilities	Quick cold weather starting and fast protection helps to extend engine life
Precisely balanced additive component system	Excellent overall lubrication and wear protection performance for many driving styles and conditions, from mild to severe, where a 5W-20 or 0W-20 is recommended

Applications

Mobil 1 0W-20 is recommended by ExxonMobil for SAE 5W-20 and 0W-20 applications in all types of gasoline fueled passenger cars, SUV's, vans, and light trucks.

- Mobil 1 0W-20 is engineered to help deliver outstanding engine protection and fuel economy benefits.
- Mobil 1 0W-20 is recommended for extreme cold conditions to help deliver quick starts and fast lubrication.
- Mobil 1 0W-20 is not recommended for 2-Cycle or aviation engines, unless specifically approved by the manufacturer.

Specifications and Approvals

This product has the following approvals:
GM dexos1:GEN2 Licensed

This product is recommended for use in applications requiring:

This product is recommended for use in applications requiring:

GM 6094M

API CF

This product meets or exceeds the requirements of:

API SN

API SM

API SL

API SJ

Ford WSS-M2C947-A

ILSAC GF-5

API SN PLUS

API SN Resource Conserving

Ford WSS-M2C947-B1

Properties and Specifications

Property	
Grade	SAE 0W-20
Kinematic Viscosity @ 100 C, mm ² /s, ASTM D445	8.7
Viscosity Index, ASTM D2270	173
Ash, Sulfated, mass%, ASTM D874	0.8
Hi-Temp Hi-Shear Viscosity @ 150 C, mPa.s, ASTM D4683	2.7
Phosphorus, mass%, ASTM D4951	0.065
Flash Point, Cleveland Open Cup, °C, ASTM D92	224
Total Base Number, mgKOH/g, ASTM D2896	8.8
Mini-Rotary Viscometer, Apparent Viscosity, -40 C, mPa.s, ASTM D4684	9200
Density @ 15.6 C, g/ml, ASTM D4052	0.841

Health and safety

Health and Safety recommendations for this product can be found on the Material Safety Data Sheet (MSDS) @ <http://www.msds.exxonmobil.com/psims/psims.aspx>

All trademarks used herein are trademarks or registered trademarks of Exxon Mobil Corporation or one of its subsidiaries unless indicated otherwise.

05-2020

Mobil Oil Lubricants LLC : 123242, Moscow, Novinsky boulevard, 31, Russia

+ 7 (095) 232 22 23

You can always contact our Technical Help Desk engineers on Mobil lubricants and services related questions: <https://www.mobil.ru/ru-ru/contact-us-technical>

Typical Properties are typical of those obtained with normal production tolerance and do not constitute a specification. Variations that do not affect product performance are to be expected during normal manufacture and at different blending locations. The information contained herein is subject to change without notice. All products may not be available locally. For more information, contact your local ExxonMobil contact or visit www.exxonmobil.com

ExxonMobil is comprised of numerous affiliates and subsidiaries, many with names that include Esso, Mobil, or ExxonMobil. Nothing in this document is intended to override or supersede the corporate separateness of local entities. Responsibility for local action and accountability remains with the local ExxonMobil-affiliate entities.

Energy lives here™

ExxonMobil

Exxon Mobil Esso XTO

© Copyright 2003-2019 Exxon Mobil Corporation. All Rights Reserved