



Une marque de **TOTAL**

EVOLUTION 900 FT

0W-40



100% synthetic and very high performance lubricant based on ELF technology. Intended for lubricating passenger cars Gasoline and Diesel engines.



APPLICATIONS

- Most recent technology engines** • Can be used for all Gasoline and Diesel engines, especially for the most recent engines.
- The most severe journeys** • Satisfy the most difficult using conditions (city, road, motorway).
- « Vigorous » driving, all times of year** • Appropriated for all driving types, in particular for sporting or intense drive and for every season.

Refer to the maintenance book of your vehicle to know the recommendation of the manufacturer

PERFORMANCES

International specifications	ACEA : A3/B4 API: SN/CF														
OEMs specifications	<table border="0"> <tr> <td>BMW</td> <td>BMW-LL-01</td> </tr> <tr> <td>VOLKSVAGEN</td> <td>VW 502.00 / 505.00</td> </tr> <tr> <td>RENAULT</td> <td>RN0700/0710</td> </tr> <tr> <td>MERCEDES BENZ</td> <td>MB-Approval 229.5 (backward compatible MB-Approval 229.3)</td> </tr> <tr> <td></td> <td>MB-Approval 226.5</td> </tr> <tr> <td>FORD</td> <td>WSS-M2C937-A</td> </tr> <tr> <td>PORSCHE</td> <td>A40</td> </tr> </table>	BMW	BMW-LL-01	VOLKSVAGEN	VW 502.00 / 505.00	RENAULT	RN0700/0710	MERCEDES BENZ	MB-Approval 229.5 (backward compatible MB-Approval 229.3)		MB-Approval 226.5	FORD	WSS-M2C937-A	PORSCHE	A40
BMW	BMW-LL-01														
VOLKSVAGEN	VW 502.00 / 505.00														
RENAULT	RN0700/0710														
MERCEDES BENZ	MB-Approval 229.5 (backward compatible MB-Approval 229.3)														
	MB-Approval 226.5														
FORD	WSS-M2C937-A														
PORSCHE	A40														

CUSTOMER BENEFITS

- Anti-wear protection** • Ensures outstanding engine longevity.
- Oxidation resistance** • Provides for extra long intervals between oil changes.
- Engine cleanliness** • Develops performance and power.
- Suitable for low and high temperatures** • Facilitates ignition in very cold weather and maintains protection of the parts even in great heat.

CHARACTERISTICS

	Method	Units	SAE Grade 0W-40
Viscosity at 40°C	ASTM D445	mm ² /s	76,41
Viscosity at 100°C	ASTM 445	mm ² /s	13,4
Viscosity index	ASTM D2270	-	183
Pour point	ASTM D97	°C	- 39
Flash point	ASTM D92	°C	231

The typical characteristics mentioned represent mean values