

PerFormance FG Hydraulic Oil ISO 22

Product Overview

PerFormance FG Hydraulic Oil ISO 22 is an NSF® H1 registered non-toxic lubricant developed for Hydraulic and pneumatic airline systems used on food, drink and pharmaceutical processing and packaging equipment. Also suitable for other hydraulic and compressed air systems where a clean, non-staining product is desired.



Features and Benefits

- Food Safe
- Audit compliant - NSF® H1 Registered
- Fully synthetic oil provides extremely wide temperature stability which ensures greatly extended servicing intervals
- Low coefficient of friction provides excellent lubrication and reduces wear
- Oxidation and Corrosion inhibited
- Low Foaming
- Reduces sludge and residue which extends maintenance intervals
- Halal Certified
- Kosher Certified

Applications

PerFormance FG Hydraulic Oil ISO 22 is suitable for all types of pneumatic airline installations and Hydraulic systems that require ISO 22 oil. Follow manufacturer's instructions.

Where application is made manually, PerFormance FG Hydraulic Oil ISO 22 needs to be applied daily as specified by the OEM.

Available Pack Sizes

Pack Size
5Ltr
20Ltr
205Ltr



Typical Properties

Appearance	Clear Fluid
Base Oil	Synthetic Oil
ISO Grade	22
Temperature range	- 20°C to + 120°C

Health and Safety

To obtain Material Safety Data Sheet (MSDS),
contact our technical team

This Information is given in good faith but without warranty as the use of the product is outside the control of Performance Fluids Ltd

Revision SB 160922

Performance Fluids Ltd

T: +44(0) 1282 878240

E: sales@performancefluids.co.uk

W: www.performancefluids.co.uk



Certificate Number: 4769-QMS-001
ISO 9001:2015
Certificate Number: 4769-EMS-001
ISO 14001:2015
Certificate Number: 4769-HSI-001
ISO 45001:2018 SSIP



Innovators in Lubrication Design