

# MOL Essence 10W-40

## semi-synthetic motor oil



MOL Essence 10W-40 is a state-of-art product made from a high performance synthetic base oil and premium quality mineral base oils that provide triple antioxidant protection, using a complex additive system, developed for passenger cars and commercial vehicles.

### Application



Naturally aspirated or turbocharged, gasoline and diesel engines in passenger cars and light commercial vehicles (<3.5 t weight)

Naturally aspirated, turbocharged and direct injection diesel engines

### Features and benefits

Triple antioxidant protection

Prevents presence of free radicals responsible for oil ageing, through triple anti-oxidant action, increasing the service life of the motor oil and the engine

Excellent shear stability

Preserves viscosity properties during the entire oil change period

Low volatility

Lowers engine oil consumption and reduces the emission of harmful substances  
Economical operation

### Specifications and approvals

Viscosity grade: SAE 10W-40  
*API SL/CF*  
ACEA A3/B4-08  
ACEA A3/B3-16  
VW 501 01/505 00

### Properties

Properties	Typical values
Density at 15°C [g/cm <sup>3</sup> ]	0,871
Kinematic viscosity at 40°C [mm <sup>2</sup> /s]	94,5
Kinematic viscosity at 100 °C [mm <sup>2</sup> /s]	14,0
Pour point [°C]	-33
Flash point (Cleveland) [°C]	220

The characteristics in table are typical values of the product and do not constitute a specification.

### Storage and handling instructions

Store in the original container in dry, properly ventilated area. Keep away from direct flame and other sources of ignition. Protect from direct sunlight.

During transport, storage and use of the product follow the work safety instructions and environmental regulations relating to mineral oil products.

For further details please read the Material Safety Data Sheet of the product.

Engine oils are finished lubricant formulations where additional additives are unnecessary and may result in unforeseeable adverse effects. The manufacturer and distributor shall not be held liable for such possible damages.

In the original container under the recommended storage conditions: 60 months

Recommended storage temperature: max. 40°C

# MOL Essence 10W-40

## semi-synthetic motor oil



### Ordering information

Custom Tariff Number 27101981

#### SAP code and packaging:

13011120	MOL Essence 10W-40 1L	1 l plastic bottle
13011121	MOL Essence 10W-40 4L	4 l plastic can
13008403	MOL Essence 10W-40 50KG	60 l steel drum
13008404	MOL Essence 10W-40 180KG	216.5 l steel drum
13008941	MOL Essence 10W-40	Road tank car (for order only)

#### Order booking:

Please contact your local distributor or sales partner for ordering details.