

# MOL Hydro SA 15

## shock-absorber oil



MOL Hydro SA 15 is a shock-absorber oil produced from highly refined base oils. It has a low viscosity and a low pour point, and contains additives that provide a balanced performance.

### Application



Oil filled shock absorbers in vehicles

Hydraulic servo equipment

### Features and benefits

Low cold viscosity

Provides appropriate operation of hydraulic control elements, even in winter period

Compatible with usual seal materials

Lower possibility of contaminant ingress and oil leaks

Outstanding oxidation stability

The natural ageing process of the oil is reduced to minimum

### Specifications and approvals

Viscosity grade: ISO VG 15  
ISO 11158 HM  
ISO-L-HM  
DIN 51524-2 (HLP)

### Properties

Properties	Typical values
Density at 15°C [g/cm <sup>3</sup> ]	0,853
Kinematic viscosity at 40°C [mm <sup>2</sup> /s]	15,5
Kinematic viscosity at 100 °C [mm <sup>2</sup> /s]	3,5
Viscosity index	105
Pour point [°C]	-30
Flash point (Cleveland) [°C]	185

The characteristics in table are typical values of the product and do not constitute a specification.

### Storage and handling instructions

Store in the original container in dry, properly ventilated area. Keep away from direct flame and other sources of ignition. Protect from direct sunlight.

During transport, storage and use of the product follow the work safety instructions and environmental regulations relating to mineral oil products.

For further details please read the Material Safety Data Sheet of the product.

In the original container under the recommended storage conditions: 48 months

Recommended storage temperature: max. 40°C

# MOL Hydro SA 15

## shock-absorber oil



### Ordering information

Custom Tariff Number 27101983

#### **SAP code and packaging:**

13006357 MOL Hydro SA 15 X1L

1 l plastic bottle

#### **Order booking:**

Please contact your local distributor or sales partner for ordering details.