

## HIGHTEC FORMULA GTS SAE 10W-40 HC

Low viscosity engine oil of viscosity grade SAE 10W-40 based on HC synthetic base oils.

### Description

HIGHTEC FORMULA GTS SAE 10W-40 HC is a high-performance engine oil of SAE grade 10W-40 produced using HC synthetic oil. Its high level of performance is achieved through the interaction of selected base oils and advanced additives. Eminently suited to Otto and diesel engines, with or without turbocharging.

### Application

HIGHTEC FORMULA GTS SAE 10W-40 HC is particularly suitable for vehicles equipped with Otto and diesel engines, with or without turbocharging. It is used in vehicles without an extended maintenance interval. The modern design of HIGHTEC FORMULA GTS SAE 10W-40 HC makes a wide range of applications possible and ensures safe operation under all operating conditions.

### The quality of this product is equivalent to EU regulations

- ACEA A3/B4
- API SN
- Fiat 9.55535-G2/D2
- MB 229.3
- Renault RN 0700/0710
- VW 502 00/505 00

### Additionally this product is recommended when the following filling instructions are required

- API CF
- BMW Longlife-98
- PSA B71 2300

### Benefits

- Eminently suitable for turbocharged engines
- Prevention of adhesion, lacquering and coking of cylinders, pistons, valves and turbochargers in a reliable manner
- Safer year-round operation due to outstanding viscosity-temperature behaviour and high shear stability
- Stable lubricating film, even with hot oil and under excessive loads
- Very low oil consumption
- High level of oxidation protection by means of selected HC synthetic oils and special additives
- Reliable protection against 'black sludge'
- Proper functioning of hydraulic tappets (hydraulic valve clearance compensation)
- Miscible and compatible with conventional and synthetic engine oils. However, in order to exploit the full product benefits of HIGHTEC FORMULA GTS SAE 10W-40 HC, a complete oil change is recommended.

### Typical characteristics

Property	Method	Unit	Value
Density at 15 °C	ASTM D-7042	g/ml	0.86
Kinematic viscosity KV 40	ASTM D-7042	mm <sup>2</sup> /s	96,8
Kinematic viscosity KV 100	ASTM D-7042	mm <sup>2</sup> /s	14,4
Viscosity index	ASTM D-7042	-	154
Flash point	ASTM D-92 / DIN EN ISO 2592	°C	244
Pour point	ASTM D-97 / DIN EN ISO 3016	°C	-32
CCS	ASTM D-5293	cP @ °C	5450 @ -25
Total base number	DIN 51639-1	mgKOH/g	8,6
HTHS	ASTM D4683	mPas	4,1

The characteristics shown are typical of current production. This data cannot be constructed as a legally binding warranty or guaranty of certain product properties or of the suitability of the product for a specific application. ROWE products are continually improved. Therefore ROWE reserves the right to change all the technical data in this product information at any time without notice. All sales and deliveries shall be subject to our current General Terms and Conditions of Sale and Terms ([www.rowe-oil.com](http://www.rowe-oil.com)).

