

MOL Dynamic Gas Eco+ 15W-40

mobile gas motor oil



MOL Dynamic Gas Eco+ 15W-40 is a high performance multi-grade engine oil composed of mineral oils produced using the most modern oil refining processes, using a multiple purpose balanced system of additives, including components that modify the flow characteristics, that ensure high performance, for use in LPG operated gas engines.

Application



Vehicles and stationary engines operating on autogas (propane-butane)

Naturally aspirated or turbocharged, gasoline, diesel and gas engines in passenger cars and light commercial vehicles (<3.5 t weight)

Features and benefits

High-level reserve of alkalinity

Persistent acid neutralization, giving improved corrosion protection

Excellent shear stability

Forms a tenacious lubricating film even under exposure to heavy stress

Exceptional thermal and oxidation stability

Perfect protection against sludge formation and sedimentation

Specifications and approvals

Viscosity grade: SAE 15W-40
ACEA E7-12
API CI-4/SL

Properties

Properties	Typical values
Density at 15°C [g/cm ³]	0,885
Kinematic viscosity at 40°C [mm ² /s]	108,5
Kinematic viscosity at 100 °C [mm ² /s]	14,4
Viscosity index	135
Pour point [°C]	-33
Flash point (Cleveland) [°C]	225
Base number (BN) [mg KOH/g]	10,7

The characteristics in table are typical values of the product and do not constitute a specification.

MOL Dynamic Gas Eco+ 15W-40

mobile gas motor oil



Storage and handling instructions

Store in the original container in dry, properly ventilated area. Keep away from direct flame and other sources of ignition. Protect from direct sunlight.

During transport, storage and use of the product follow the work safety instructions and environmental regulations relating to mineral oil products.

For further details please read the Material Safety Data Sheet of the product.

Engine oils are finished lubricant formulations where additional additives are unnecessary and may result in unforeseeable adverse effects. The manufacturer and distributor shall not be held liable for such possible damages.

In the original container under the recommended storage conditions: 60 months

Recommended storage temperature: max. 40°C

Ordering information

Custom Tariff Number 27101981

SAP code and packaging:

13006098 MOL Dynamic Gas Eco+ 15W-40 X1L

1 l plastic bottle

Order booking:

Please contact your local distributor or sales partner for ordering details.