



RAVENOL Calibration Fluid



SPECIFICATIONS ISO 4113 | SAE J967D

RECOMMENDATIONS MB 133.0 | BOSCH VS 15665-OL-CV |
KORROSIONSSCHUTZÖL ZUR INNENKONSERVIERUNG VON
KRAFTSTOFFSYSTEMEN VON MTU

RAVENOL Calibration Fluid is a test fluid for the calibration of diesel injection pumps and as a corrosion preventive oil for the internal preservation of fuel systems.

ART.-NR. 1350130

10 L | 1350130-010
20 L | 1350130-020
20 L | 1350130-B20
1000 L | 1350130-700

Application Notes

RAVENOL Calibration Fluid V is used as a test fluid for the calibration of diesel injection pumps and as a corrosion preventive oil for the internal preservation of fuel systems.

Characteristics

RAVENOL Calibration Fluid offers:

- Excellent wear protection
- Excellent corrosion protect
- Low tendency to foam

Property	Unit	Data	Audit
Density at 20°C	kg/m ³	823	EN ISO 12185
Colour		hellbraun	visual
Viscosity at 40°C	mm ² /s	2,53	DIN 51 562
Pourpoint	°C	-39	DIN ISO 3016
Flash point (COC)	°C	120	DIN ISO 2592
TBN base number	mg KOH/g	0,1	ASTM D2896



All information correspond to the best of our knowledge to the actual situation of the cognitions and our development. Subject to alterations. All references made to DIN-norms are only for the description of the goods. There is no guarantee. In case there will be any problems please contact the technical service.

Release: : 20. January 2020