

MOL Essence Multi Gas 5W-40

mobile gas motor oil



MOL Essence Multi Gas 5W-40 is a low ash (SAPS) synthetic engine oil produced with the use of a complex additive system that provides triple antioxidant protection and the high engine oil performance levels required by European and US specifications, developed for the most recent gas fueled passenger cars and small commercial vehicles.

Application



Special CNG and LPG fueled passenger cars and vans.

Naturally aspirated or turbocharged, gasoline and diesel engines in passenger cars and light commercial vehicles (<3.5 t weight)

Vehicles equipped with a diesel particulate filter (DPF) or three-way catalyst

Short and long haul passenger car and light (<3.5 t) commercial vehicle engines

Features and benefits

Triple antioxidant protection

Prevents presence of free radicals responsible for oil ageing, through triple anti-oxidant action, increasing the service life of the motor oil and the engine

High-level reserve of alkalinity

Persistent acid neutralization, giving improved corrosion protection

Low volatility

Lowers engine oil consumption and reduces the emission of harmful substances
Economical operation

Low sulphated ash, sulphur and phosphorus content (Low SAPS)

Long lifetime of catalysts and diesel particulate filter

Extremely long oil lifetime

Frequency of downtimes, operational costs, and environmental impact can be reduced

Specifications and approvals

Viscosity grade: SAE 5W-40
ACEA C3-16
API SN/CF
API SM/CF
VW 502 00/505 00
VW 505 01
Ford WSS M2C917-A
Porsche A40
Renault RN0710
Fiat 9.55535-S2

MOL Essence Multi Gas 5W-40

mobile gas motor oil



Properties

| Properties | Typical values |
|--|----------------|
| Density at 15°C [g/cm ³] | 0,854 |
| Kinematic viscosity at 40°C [mm ² /s] | 86,7 |
| Kinematic viscosity at 100 °C [mm ² /s] | 14,1 |
| Pour point [°C] | -39 |
| Flash point (Cleveland) [°C] | 240 |
| Base number (BN) [mg KOH/g] | 8,1 |

The characteristics in table are typical values of the product and do not constitute a specification.

Storage and handling instructions

Store in the original container in dry, properly ventilated area. Keep away from direct flame and other sources of ignition. Protect from direct sunlight.

During transport, storage and use of the product follow the work safety instructions and environmental regulations relating to mineral oil products.

For further details please read the Material Safety Data Sheet of the product.

Engine oils are finished lubricant formulations where additional additives are unnecessary and may result in unforeseeable adverse effects. The manufacturer and distributor shall not be held liable for such possible damages.

In the original container under the recommended storage conditions: 60 months

Recommended storage temperature: max. 40°C

Ordering information

Custom Tariff Number 27101981

SAP code and packaging:

13010095 MOL Essence Multi Gas 5W-40 X1L

1 l plastic bottle (for order only)

Order booking:

Please contact your local distributor or sales partner for ordering details.