



Corrosion Inhibitor S 226

Corrosion Inhibitor for water based metalworking fluid

Description

Castrol Corrosion Inhibitor S 226 is a highly effective low foaming water soluble corrosion inhibitor especially recommended for yellow metals. It can be used in single sump machines as well as central systems.

Application

Castrol Corrosion Inhibitor S 226 can be used when corrosion protection of existing product needs to be improved. It can be used in all water based metalworking fluids including solubles, synthetics, industrial cleaners and deformation products.

Conditions of Use

Castrol Corrosion Inhibitor S 226 should only be used upon recommendation of Castrol's Service Representative.

Addition between 0,02 - 0,1% is recommended depending on corrosion level.

Appearance = clear yellow liquid Density at 15°C kg/m³ = 1200 - 1220 pH at 5% = 8.2 - 8,8

Storage

To avoid product deterioration, keep the container/drum tightly sealed always. Prevent any frost and water ingress. Store it in a cool and dry place away from direct sunlight. It is preferable to store the product indoors always. For more details, please refer the product safety data sheet.

Corrosion Inhibitor S 226

01 Sep 2016

Castrol, the Castrol logo and related marks are trademarks of Castrol Limited, used under licence.

This data sheet and the information it contains is believed to be accurate as of the date of printing. However, no warranty or representation, express or implied, is made as to its accuracy or completeness. Data provided is based on standard tests under laboratory conditions and is given as a guide only. Users are advised to ensure that they refer to the latest version of this data sheet. It is the responsibility of the user to evaluate and use products safely, to assess suitability for the intended application and to comply with all applicable laws and regulations. Material Safety Data Sheets are available for all our products and should be consulted for appropriate information regarding storage, safe handling, and disposal of the product. No responsibility is taken by either BP plc or its subsidiaries for any damage or injury resulting from abnormal use of the material, from any failure to adhere to recommendations, or from hazards inherent in the nature of the material. All products, services and information supplied are provided under our standard conditions of sale. You should consult our local representative if you require any further information.

Castrol (UK) Limited, PO BOX 352, Chertsey Road, Sunbury On Thames, Middlesex, TW16 9AW

Orders/Enquiries: 0345 9645111 Technical Enquiries: 0345 082 1719

www.castrol.com/industrial