

MOL Essence Diesel 10W-40

semi-synthetic diesel motor oil



MOL Essence Diesel 10W-40 is a state-of-art product made from high performance synthetic and highly refined base oils that provide triple antioxidant protection, using a complex additive system, developed for diesel passenger cars and small commercial vehicles.

Application



Short and long haul passenger car and light (<3.5 t) commercial vehicle engines

Naturally aspirated, turbocharged and direct injection diesel engines

Features and benefits

Triple antioxidant protection

Prevents presence of free radicals responsible for oil ageing, through triple anti-oxidant action, increasing the service life of the motor oil and the engine

Excellent shear stability

Preserves viscosity properties during the entire oil change period

Low volatility

Lowers engine oil consumption and reduces the emission of harmful substances
Economical operation

Excellent soot handling

Protection against soot deposits and bore polishing

Specifications and approvals

Viscosity grade: SAE 10W-40
ACEA A3/B4-08
ACEA A3/B3-16
API CF/SL
VW 505 00

Properties

| Properties | Typical values |
|--|----------------|
| Density at 15°C [g/cm ³] | 0,871 |
| Kinematic viscosity at 40°C [mm ² /s] | 94,5 |
| Kinematic viscosity at 100 °C [mm ² /s] | 14,0 |
| Pour point [°C] | -33 |
| Flash point (Cleveland) [°C] | 220 |

The characteristics in table are typical values of the product and do not constitute a specification.

MOL Essence Diesel 10W-40

semi-synthetic diesel motor oil



Storage and handling instructions

Store in the original container in dry, properly ventilated area. Keep away from direct flame and other sources of ignition. Protect from direct sunlight.

During transport, storage and use of the product follow the work safety instructions and environmental regulations relating to mineral oil products.

For further details please read the Material Safety Data Sheet of the product.

Engine oils are finished lubricant formulations where additional additives are unnecessary and may result in unforeseeable adverse effects. The manufacturer and distributor shall not be held liable for such possible damages.

In the original container under the recommended storage conditions: 60 months

Recommended storage temperature: max. 40°C

Ordering information

Custom Tariff Number 27101981

SAP code and packaging:

| | | |
|----------|---------------------------------|--------------------|
| 13011130 | MOL Essence Diesel 10W-40 1L | 1 l plastic bottle |
| 13011131 | MOL Essence Diesel 10W-40 4L | 4 l plastic can |
| 13008787 | MOL Essence Diesel 10W-40 180KG | 216.5 l steel drum |

Order booking:

Please contact your local distributor or sales partner for ordering details.